

PRODUCTS

# Framery 2Q

Not only a pod, but a full-sized meeting room




Designed for 4-6 people, **Framery 2Q** meeting pod is the ideal place to co-create, brainstorm and meet together. Framery's superior sound insulation and echo-free acoustics ensure that your meetings won't disturb the office – and the office noise won't disturb you.

**framery**

# Perfect for you

How do you work best? Choose the interior layout that best suits your needs.



## Framery 2Q Huddle

### Huddle up for your next team meeting!

Framery 2Q Huddle is the ideal setup for meetings - whether attendees are present, joining remotely, or anything in between. Gather your team around the table where everyone fits comfortably - even with their laptops! The spacious pod allows everyone to move around freely, and bring additional seating if needed. Optimize your meetings with a screen bracket and whiteboard set on the opposite wall to ensure that everyone present - physically or virtually - shares the same vision.



## Framery 2Q Lounge

### Living room in your office

Framery 2Q Lounge interior layout provides a more casual environment. It's perfect for relaxed company meetings, a calm space to retreat to during the workday, or an area for socialization. Custom-designed Clint Sofa, large whiteboard, free-standing Piaggio table and a wall shelf create a functional yet relaxed setting. The adjustable airflow and lighting create a pleasing working atmosphere. Additional options include a display bracket on the wall for a TV or a booking bracket ready option for the door for reserving the pod.


## Framery 2Q Without Furniture

### Have it in your style


Choose the Framery 2Q meeting pod without furniture to furnish it the way you like. The superb sound insulation ensures you and your team total sound privacy and the adjustable airflow keeps the atmosphere fresh. The power column is a fixed component with 3 power sockets and charging twin USB (A+C), also providing an option for a display bracket or a whiteboard. A low doorstep makes the Framery 2Q wheelchair accessible.

## Colors

### Exterior




### Frame



### Table




### Clint Sofa upholstery



## Technical specifications

- Size** 222 cm x 235 cm x 280 cm (h, w, d)  
87.4 in x 92.5 in x 110.4 in (h, w, d)
- Weight** 950 kg / 2094 lb (without furniture)
- Ventilation space** Minimum recommended space for air to circulate  
Above: 15 cm / 5.9 in
- Acoustics** 29 dB (Speech level reduction according to ISO 23351-1 testing method)
- Airflow** Total airflow is 121 l/s, 256 CFM (436 m<sup>3</sup>/h)  
On standby mode the fans are working on 25 % of the maximum power.
- Lighting** LED lights: 4500 K and 400 lux
- Exterior materials** Exterior: Painted sheet metal  
Glass: Sound control laminated glass (5 + 5 mm)  
Frame: Formica laminate on birch plywood with varnish trim.
- Interior materials** Solid walls and roof: A sandwich element of sheet metal, birch plywood, recycled acoustic foam and acoustic felt.  
An anti-static and stain resistant low loop pile carpet for interior floor.  
Table: White Formica laminate on birch plywood with varnish trim.



## Certificates



## Specifications

### Framery 2Q Huddle

#### Exterior

222 cm × 235 cm × 280 cm (height, width, depth)  
87.4 in × 92.4 in × 109.2 in (height, width, depth)

#### Interior

210 cm × 215 cm × 267 cm (height, width, depth)  
81.6 in × 84 in × 104.4 in (height, width, depth)

#### Doorway

86 cm wide / 33.6 in wide

#### Lighting

Led light: 4500 K and 400 lux

#### Ventilation space

(Minimum recommended space for air to circulate)

Above: 15 cm / 5.9 in

#### Power consumption

42 W while in use (Standard configuration)

- LED lights: 24 W

- Fans in total: 18 W

5 W in standby mode

Input: 100-240 VAC, 8.0 A, 50-60 Hz


#### Huddle table

140 cm × 86 cm (length, width) / 54 in × 33.6 in (length, width)

Working height options: 72 cm (28.3 in) and 110 cm (43.3 in)

#### Outlets

4 power sockets, USB-A+C, HDMI, Optional: LAN (replaces 1 power socket)



#### Output values

Output VAC (power socket): 100-240 VAC, 6,6 A, 50-60 Hz

Output USB (TUF) charging:

Maximum combined output of 5 A at 5 VDC (25W)

#### Screen specifications

Display bracket on the table wall. Possibility to mount a display on the opposite wall. Screen not included.

Screen specifications:

- Maximum display size: 50"

- Maximum weight: 30 kg / 66 lbs

VESA support:

100 × 100, 100 × 150, 150 × 100, 200 × 100,

100 × 200, 200 × 200, 300 × 200, 400 × 200

Power cord can be led out of the bottom from backside of the pod, the length is 3,5m / 136.8 in

All electric components can be changed if there is a malfunction. Power consumption is a constant value that is determined by the power usage of the pods' internal components (electric unit, motion detector, light and fans). Framery's products can be plugged into a wall socket. The pods have their own power supplies that give 24 V DC to the lights and 12 V DC to the fans. The lights and fans are operated by a motion detector. Inside the pods, there are country-specific power outlets for charging mobile devices.

### Framery 2Q Without Furniture

#### Exterior

222 cm × 235 cm × 280 cm (height, width, depth)  
87.4 in × 92.4 in × 109.2 in (height, width, depth)

#### Interior

210 cm × 215 cm × 267 cm (height, width, depth)  
81.6 in × 84 in × 104.4 in (height, width, depth)

#### Doorway

86 cm wide / 33.6 in wide

#### Lighting

Led light: 4500 K and 400 lux

#### Ventilation space

(Minimum recommended space for air to circulate)

Above: 15 cm / 5,9 in

#### Power consumption

42 W while in use (Standard configuration)

- LED lights: 24 W


- Fans in total: 18 W

5 W in standby mode

Input: 100-240 VAC, 8.0 A, 50-60 Hz

#### Outlets

3 power sockets, USB-A+C, Optional: LAN (replaces 1 power socket)



#### Output values

Output VAC (power socket): 100-240 VAC, 6,6 A, 50-60 Hz

Output USB (TUF) charging:

Maximum combined output of 5 A at 5 VDC (25W)

Power cord can be led out of the bottom from backside of the pod or from the ceiling, the length is 3,5m / 136.8 in

All electric components can be changed if there is a malfunction. Power consumption is a constant value that is determined by the power usage of the pods' internal components (electric unit, motion detector, light and fans). Framery's products can be plugged into a wall socket. The pods have their own power supplies that give 24 V DC to the lights and 12 V DC to the fans. The lights and fans are operated by a motion detector. Inside the pods, there are country-specific power outlets for charging mobile devices.

## Specifications

### Framery 2Q Lounge

#### Exterior

222 cm × 235 cm × 280 cm (height, width, depth)  
87.4 in × 92.4 in × 109.2 in (height, width, depth)

#### Interior

210 cm × 215 cm × 267 cm (height, width, depth)  
86.4 in × 92.4 in × 109.2 in (height, width, depth)

#### Doorway

86 cm wide / 33.6 in wide

#### Lighting

Led light: 4500 K and 400 lux

#### Ventilation space

(Minimum recommended space for air to circulate)

Above: 15 cm / 5.9 in

#### Power consumption

42 W while in use (Standard configuration)

- LED lights: 24 W

- Fans in total: 18 W

5 W in standby mode

Input: 100-240 VAC, 8.0 A, 50-60 Hz

#### Lounge

2 power sockets, USB-A+C

Optional: Data Cartridge with two LAN ports

#### Lounge wall shelf

175 cm (length) / 68.4 in (length)

#### Lounge Piaggio table

63 cm × 42 cm × 36 cm (height, width, depth)


24 in × 15.6 in × 13.2 in (height, width, depth)

#### Outlets

6 power sockets, 2 USB-A+C, Optional: Data Cartridge with 2 LAN ports

Power cord can be led out of the bottom from backside of the pod, the length is 3,5m / 136.8 in

All electric components can be changed if there is a malfunction. Power consumption is a constant value that is determined by the power usage of the pods' internal components (electric unit, motion detector, light and fans). Framery's products can be plugged into a wall socket. The pods have their own power supplies that give 24 V DC to the lights and 12 V DC to the fans. The lights and fans are operated by a motion detector. Inside the pods, there are country-specific power outlets for charging mobile devices.



#### Whiteboard

240 cm × 100 cm (width, height) / 93.6 in × 38.4 in (width, height)

#### Output values

Output VAC (power socket): 100-240 VAC, 6,6 A, 50-60 Hz

Output USB (TUF) charging:

Maximum combined output of 5 A at 5 VDC (25W)

#### Screen specifications (Optional)

Located on the centre of the lounge whiteboard. Screen not included.

Screen specifications:

- Maximum display size: 50"

- Maximum weight: 30 kg / 66 lbs


- Tilting angle: +5/-8°

VESA support:

100 × 100, 100 × 150, 150 × 100, 200 × 100,

100 × 200, 200 × 200, 300 × 200, 400 × 200

## Furnitures



#### Framery 2Q Huddle

Standard and high table (72 cm and 110 cm). Gather your team of four around a spacious table where everyone fits comfortably, laptops included. There is enough space for overflow seating if more team mates drop by.



#### Framery 2Q Lounge

Custom-designed Clint Sofa, large whiteboard, free-standing Piaggio table and a wall shelf were designed to create a functional yet relaxed setting for meetings and brainstorming sessions.

Power cord can be led out of the bottom from backside of the pod or from the ceiling, the length is 3,5m / 136.8 in

All electric components can be changed if there is a malfunction. Power consumption is a constant value that is determined by the power usage of the pods' internal components (electric unit, motion detector, light and fans). Framery's products can be plugged into a wall socket. The pods have their own power supplies that give 24 V DC to the lights and 12 V DC to the fans. The lights and fans are operated by a motion detector. Inside the pods, there are country-specific power outlets for charging mobile devices.

# Functionalities

## Always included



### Control panel for ventilation and lighting

The control panel allows you to adjust ventilation and lighting inside the pod. It is a standard functionality included with all Framery 2Q configurations. For Framery 2Q Huddle and Lounge the control panel is installed on doorway frame; In Framery 2Q Without Furniture the control panel is in the middle column next to back glass.



**Self-closing hinges** are used to make sure the door is not blocking passageways. Self-closing hinges are a type of hinge that has a spring built into it. Available for left-handed door. Self-closing hinges are included as standard on all Framery 2Q configurations. Includes set of black hinges for the door.

## Included in Huddle




**Screen bracket** is located on the table wall. It is possible also to mount the bracket on the opposite wall. Option includes mounting plate for the wall, and mounting plate for the screen. Screen is not included. **Screen specifications:** Max. display size 50", Max. weight: 30 kg / 66 lbs **Vesa support:** 100 x 100, 100 x 150, 150 x 100, 200 x 100, 100 x 200, 200 x 200, 300 x 200, 400 x 200. As an option, compatible with Framery 2Q Lounge and Without Furniture.



### Power outlet

Peak socket is installed on Huddle table. It includes four power, two charging USB (C+A) and a HDMI socket. Optional LAN ports are available (replaces one of the power sockets).

## Included in Lounge



**Whiteboard** is attached to either side of the non-glass walls. Dimensions of the whiteboard are 100 cm x 240 cm / 39.4 in x 94.5 in (height, width). Option includes the whiteboard and the cork center.

As an option, compatible also with Framery 2Q Huddle and Without Furniture.



**Piaggio table** is a movable table with tabletop dimensions of 36 cm x 42 cm / 14.2 in x 16.5 in. Table height: 62 cm / 24.4 in. One Piaggio table is included in Framery 2Q Lounge. As an option, additional tables can also be selected. Compatible also with Framery 2Q Without Furniture.



**Power outlets** in Framery 2Q Lounge are located under the lounge shelf table and the sofa. There are six power and two charging USB (C+A) sockets. Optional LAN ports are available.

## Optional functionalities



**Booking bracket** is a universal booking tablet bracket with a plywood surface attached to the door locking plate. Two sizes available to fit your device. Option includes the bracket and kit required for attachment. Customer acquires the booking tablet and cover for it which is mounted to the bracket. Compatible with all Framery 2Q configurations. **Bracket dimensions:** Small 12 cm x 23 cm / 4.7 x 9.1 in Large 22cm x 30 cm / 8.7 x 11.8 in



**Smart Lock Compatible** is a kit of parts that allows customer selected smart lock and key to be installed. Compatible with all configurations of Framery 2Q. Option includes kit shown in picture. Smart lock itself is acquired by the customer.



**Copper-plated door handle** Copper has been used for health purposes since ancient times. According to a study by Centers for Disease Control and Prevention (CDC), viruses disintegrate quicker after landing on copper surfaces than on plastic or stainless steel surfaces. Compatible with all configurations of Framery 2Q. Option includes copper-plated door handle.



**Anti-microbial, non-toxic polyester fabric** Anti-microbial, waterproof, bleach cleanable, stain resistant and durable polyester fabric. Our non-toxic material is safe and ISO 10993-5:2009 tested.